South Carolina Manufactured Housing Energy Efficient Label Disposition Form



Manufacturer Manufactured Housing License Number			Contact	
			Email	
Mailing Address		Telephone		
City	State	Zip	Fax	
Energy Efficiency Label Number	Se	rial Number	HUD Label Number	Retailer and Location Shipped to
1.				
2.				
3.				
4.				
5.				
6.				
7.				
8.				
9.				
10.	providing ov	vn form or if	additional space is neede	ed to list home information

For a manufactured home to meet South Carolina's standards for energy efficiency, the home must have the following:

- 1. Storm or double pane glass windows;
- 2. Insulated or storm doors;
- 3. A minimum thermal resistance rating of R-11 for walls, R-19 for floors, and R-30 for ceilings OR allowances in the energy efficiency levels for walls, floors, and ceilings, so long as the heat loss does not exceed that calculated using the R levels stated above. These heat loss calculations are based on the current edition of the American Society of Heating, Refrigeration, and Air-Conditioning Engineers Guide (ASHRAE) at the time of the home's manufacture.

The following statement (along with signature and printed name) must be included if providing own form:

I hereby attest that each requested energy efficiency label will be affixed inside the breaker box of the appropriate unit as identified by the serial number on the energy efficient label.

Signature:	Date:
(Must be signed by company official)	

Please print above name:

Please complete this form and email or mail to:

EnergyCS@ORS.SC.GOV
Energy Office, South Carolina Office of Regulatory Staff
1401 Main Street, Suite 900,
Columbia, SC 29201
(803) 737-0800